IRSTOCK 1260





IRMATIC Sp. z o.o. Sobienki 30, 08-445 Osieck biuro@irmatic.pl NIP: 123 149 55 51



www.irmatic.com



IRSTOCK 1260

Innovative and reliable Multifunctional Vending Machine, compliant with the concept of industry 4.0.



ADVANTAGES

- 24/7 access.
- Drop in the consumption of products by up to 50%.
- Very large capacity, up to 1260 compartments in the machine.
- 4 options for loading products into the machine.
- 21" touch screen with modern and intuitive interface.
- **9 configurations** for height and width of compartments.
- Built-in RFID reader, barcode and **QR code scanner**.
- Monitoring of current status via the IRSystem web application.
- Modularity allows to combine devices into sets.

IRSYSTEM APPLICATION


We offer **proprietary IRSYSTEM** software tailored to the individual needs of the customer for each vending machine, which opens up **unlimited possibilities for remote process management.** IRSYSTEM enables **data migration** and fast communication between the server and machine.

- possibility of **integration** with systems such as ERP, GERP, SAP, etc.
- generating of **automatic reports** and orders
- actual preview of the inventories available in the machine
 management of authorisation of employee access to the



IRSTOCK 1260 is a modern and **self-service** vending machine used for product distribution. The rotating, sturdy drum gives you the ability to storage up to **1260 unique items.** Ease of operation is provided by **21'' touch screen** with modern and intuitive interface. Four product **loading options** enable even faster and simpler filling the machine. The IRSTOCK 1260 has a built-in **RFID reader**, barcode and **QR code scanner**.

TECHNICAL SPECIFICATIONS				
Height [mm]	2 000			
Width [mm]	1 360			
Depth [mm]	1 100			
Voltage [V]	230 VAC - 50 Hz			
Power usage [W]	5/80			
Max. drum load [kg]	400			
Dry mass [kg]	670			
Temp. [°C]	from 5 to 70			
DRUM CONFIGURATIONS				



COMPARTMENS CONFIGURATIONS AND DIMENSIONS				
NUMBER OF COMPARTMENTS	A HEIGHT [MM]	B WIDTH [MM]	C DEPTH [MM]	D WIDTH [MM]
1260	80	50	405	12
840	80	80	405	18
420	80	160	405	35
660	160	50	405	12
440	160	80	405	18
220	160	160	405	35
420	245	50	405	12
280	245	80	405	18
140	245	160	405	35