MEDDRAWER









MEDDRAWER

Innovative machine for storage, distribution and return of medical and pharmaceutical products.



IRSYSTEM APPLICATION

- 24/7 access.
- **Drop in** the consumption of products by **up to 50**%.
- Extensive product returns function.
- **Very large capacity,** 1792 lockers in the machine.
- **2 types of drawers** within one machine.
- Multiple configurations available.
- **21" touch screen** with modern and intuitive interface.
- Configuration as required.
- **Built-in RFID** reader, barcode and **QR code scanner**.
- Monitoring of current status via the IRSystem web application.
- Modularity allows to combine devices into sets.

MEDSYSTEM APPLICATION


We offer proprietary MEDSYSTEM software tailored to the individual needs of the customer for each vending machine, which opens up unlimited possibilities for remote process management. MEDSYSTEM enables data migration and fast communication between the server and machine.

- possibility of integration with systems such as ERP, GERP, SAP, etc.
- generating of **automatic reports** and orders
- actual **preview of the inventories** available in the machine
- management of authorisation of employee access to the vending machine



MEDDRAWER is a modern, self-service vending machine for product distribution. The design, based on a drawer system, offers the possibility of storage of up to 1,792 unique items of different sizes. Ease of operation is provided by 21" touch screen with modern and intuitive interface. Two product loading options enable even faster and simpler filling the machine. The MEDDRAWER has a built-in RFID reader, barcode and QR code scanner which supports the product return function.

TECHNICAL SPECIFICATIONS		
Height [mm]	1795	
Width [mm]	980	
Depth [mm]	600	
Voltage [V]	230 VAC - 50 Hz	
Pover usage [W]	5/80	
Max. drawer load [kg]	100	
Weight [kg]	250	
Temp. [°C]	from 5 to 70	



LOCKER CONFIGURATIONS IN THE DRAWER			
NUMBER OF COMPARTMENTS	A HEIGHT [MM]	B WIDTH [MM]	C DENSITY [MM]
128	57	44	52 or 129
64	57	100	52 or 129
32	116	100	52 or 129
16	116	212	52 or 129
8	116	463	52 or 129
32	233	44	52 or 129
16	233	212	52 or 129
4	233	436	52 or 129
16	468	44	52 or 129
8	468	100	52 or 129
4	468	212	52 or 129
2	468	436	52 or 129