


# IRLOCKER



COST  
REDUCTION



SAVING  
TIME



CONTROL



REPORTING



24/7 ACCESS



# IRLOCKER

Innovative and reliable **Multifunctional Vending Machine**, compliant with the concept of industry 4.0.




## ADVANTAGES

- ▶ **24/7 access.**
- ▶ **Drop in** the consumption of products by **up to 50%**.
- ▶ Extensive **product returns** function.
- ▶ Power tool **charging capability**.
- ▶ **Large capacity, 72 storage** compartments in the machine or **1200 including drawers**.
- ▶ **2 options for loading** products into the machine.
- ▶ **21" touch screen** with modern and intuitive interface.
- ▶ **Configuration** as required.
- ▶ Built-in **RFID reader**, barcode and **QR code scanner**.
- ▶ **Monitoring of current status** via the IRSystem web application.
- ▶ **Modularity** allows to combine devices **into sets**.

## IRSYSTEM APPLICATION

We offer **proprietary IRSYSTEM software** tailored to the individual needs of the customer for each vending machine, which opens up **unlimited possibilities for remote process management**. IRSYSTEM enables **data migration** and fast communication between the server and machine.

- possibility of **integration** with systems such as ERP, GERP, SAP, etc.
- generating of **automatic reports** and orders
- actual **preview of the inventories** available in the machine
- **management of authorisation** of employee access to the vending machine




**IRLOCKER** is a **modern and self-service** vending machine used for product distribution. The modular design gives the possibility to store **up to 72\* unique items of different sizes**. Ease of operation is provided by **21" touch screen** with modern and intuitive interface. **Two product loading options** enable even faster and simpler filling the machine. The IRLOCKER has a built-in **RFID reader**, barcode and **QR code scanner** which supports **the product return function**.

\*1200 - maximum number of lockers in combination with drawers

## TECHNICAL SPECIFICATIONS

Height [mm]	2 000
Width [mm]	1 120
Depth [mm]	600
Voltage [V]	230 VAC - 50 Hz
Pover usage [W]	5/80
Max. load of the locker [kg]	50*
Max. drawer load [kg]	100
Weight [kg]	295
Temp. [°C]	from 5 to 70



## LOCKER CONFIGURATIONS

NUMBER OF LOCKERS	A HEIGHT [MM]	B WIDTH [MM]	C DEPTH [MM]
72	123,6	143,7	553
36	277,2	143,7	553
18	277,2	328,7	553
12	430,8	328,7	553
9	584,4	328,7	553
6	891,6	328,7	553